

# Cargo Doors One End High Cube Dry Freight ISO Cargo Container 40'(L) x 8'(W) x 9'6"(H)



# PRODUCT FEATURES

### STANDARD FEATURES

- Corrugated steel sides, roof, and swing doors on (1) end
- Two-way forklift pockets (one way new containers only)
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Wall tie down steel lashing rings, 4,000 lbs. cap. each (40 total) tested at 6,000 lbs.
- · Corner castings (8 total)
- · ISO vents (4 total)



#### HIO # 458-0550.80

# ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

| CX40ST  | LENGTH (+0/-6) |            | HEIGHT (+0/-5) |             | WIDTH (+0/-5) |           | DOOR OPENING (+0/-5) |            |
|---------|----------------|------------|----------------|-------------|---------------|-----------|----------------------|------------|
|         | Exterior       | Interior   | Exterior       | Interior    | Exterior      | Interior  | Height               | Width      |
| Ft. in. | 40' 0"         | 39' 5 3/4" | 9' 6"          | 8' 10 1/16" | 8' 0"         | 7' 8 1/2" | 8' 5 3/4"            | 7' 8 1/16" |
| Metric  | 12,192         | 12,033     | 2,896          | 2,460       | 2,438         | 2,350     | 2,585                | 2,338      |
|         | TARE WEIGHT    |            | PAYLOAD        |             | GROSS WEIGHT  |           | CUBIC CAPACITY       |            |
| Lbs.    | 8,530          |            | 58,670         |             | 67,200        |           | 2,690 cu. ft.        |            |
| Kas.    | 3.870          |            | 26.610         |             | 30.480        |           | 76.2 cu. m           |            |

ISO 9001

CERTIFIED QUALITY
MANAGEMENT SYSTEM





ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS